

WS-J60 series portable industrial endoscope




Professional industrial endoscope solution supplier

To be as your wish

More efficient detection

WS-J series is mainly used to assist criminal investigation, EOD, security inspection, anti-smuggling, search and rescue and other related testing work. , It has the characteristics of light overall weight, high strength, single-person operation, easy to carry, simple operation, sturdy and durable, and strong concealment.



Red and white light for optional



Recording function for optional



Quick to change probes



Modular battery pack



5 inch screen, Visible in sunlight













WIFI wireless transmission for optional












Host	Size	350*155*59mm
	Display	5 inch industrial grade screen
	Output port	TF card, HDMI port, Micro USB
	Memory card	Standard 32G TF card, Support up to 128G
	Power	Dedicated rechargeable lithium battery pack, which can be recharged online and has a long battery life ≥ 4 hours
	IP grade	IP54
	Working temperature	-10°C~50°C
	Storage temperature	-20°C~60°C
	Relative humidity	Max 90%, no condensation
	Weight	≤ 0.8 kg(Weight with battery)
System	Operation system	Multifunctional operating system
	Operation method	Button navigation, dual camera and video buttons
	Support function	With freeze, zoom, photo, flip, video playback, analog ruler functions
	File format	Image JPEG (JPG) format, Video AVI format
	Language	Chinese English etc 7 languages
Packing Case	Weight	
	L*M*H	

Camera and Probe

Model		WS-J60					
		WS-J6010	WS-J6020	WS-J6030	WS-J6040	WS-J6050	WS-J6060
Lens	Direction	Direct view/Side view/Double view					
	View angle(θ)	75°/84°					
	DOF	50mm~ ∞					
	Resolution	1000000					
	Lighting type	Infrared illumination (Wavelength distance: 10m)		940nm without red exposure 850nm with red exposure			
	White light optical fiber illumination						
Probe	Light(L)	13 \pm 0.5mm					
	Diameter(D)	6mm					
	Articulating	360°full way articulating					
	Bending angle(α)	170° \pm 10°	160° \pm 10°	140° \pm 10°	120° \pm 10°	110° \pm 10°	
	IP Grade	IP67					
	Working temperature	-20°C~70°C					
Inserting tube	Length	1m	2m	3m	4m	5m	6m
	Material	Soft (tungsten braided tube)					

	WS-J (Direct view)	WS-JC (Side view)
Lens Direction		
View angle(θ)		
DOF		
Probe length(L)		
Probe diameter(D)		
360°articulating		
Bend angle(α)		

Packing list

No	Name	PCS	Unit	备注
1	Host	1	pcs	
2	Battery	1	pcs	
3	Packing case	1	pcs	
4	Memory card	1	pcs	
5	Card reader	1	pcs	
6	Tripod	1	pcs	
7	Data line	1	pcs	
8	HDMI cable	1	pcs	
9	Charger	1	pcs	
10	Warranty card	1	pcs	
11	User manual	1	pcs	<p style="text-align: center; font-size: small;">Industrial Endoscope User Manual</p> 
12	Guarantee Card	1	pcs	